Material Safety Data Sheet



BA180 Chrome Oxide

Clays Glazes Colours

Company Details Walker Ceramics 5 McLellan St, Bayswater, Victoria 3153, Australia

Telephone (03) 8761 6322 Fax (03) 8761 6344

Email sales@walkerceramics.com.au Website www.walkerceramics.com.au

Date Of Issue: March 2019

IDENTIFICATION	
Product Name	Chrome Oxide
Other Names	None
Manufacturers Product Code	BA180
UN Number	None
Dangerous Goods Class & Subsidiary Code	None
Hazchem Code	None
Poisons Schedule Number	None
CAS Number	1308-38-9
Use(s)	Used in ceramics and pottery.

PHYSICAL DESCRIPTION / PROPERTIES	
Appearance	Green odourless coloured powder.
Boiling Point / Melting Point	>1000°C
Vapour Pressure	Not applicable
Specific Gravity	Not applicable
Flashpoint	Not applicable
Flammability Limits	Not applicable
Solubility in Water	Immiscible.
Other Properties	

INGREDIENTS		
Chemical Name	CAS Number	Proportion (%)
Chrome oxide	1308-38-9	100

HEALTH HAZARD INFORMATION	
Acute	
Swallowed	This solid/dust is harmful to the gastrointestinal tract. May cause vomiting & general pain, by ingestion of large amounts.
Eye	The dust may produce irritation of the eyes.
Skin	This product is abrasive and may cause irritation and dryness of the skin.
Inhaled	This product as dust may cause respiratory irritation to the upper respiratory tract and lungs.
Chronic	Principal route of exposure is ingestion. This product is acutely toxic and may cause general distress and progress to severe illness and possible death.

FIRST AID	
Swallowed	Contact POISON INFORMATION CENTRE and seek medical advice.
Eye	Immediately hold eyes open and wash continuously with running water for at least 15 minutes. Ensure irrigation includes under eyelids. TRAINED STAFF ONLY ARE TO ATTEMPT THE REMOVAL OF CONTACT LENSES. Seek medical attention without delay.
Skin	Remove all contaminated clothing immediately, including footwear and wash thoroughly before re-use. Wash affected areas thoroughly with soap and water if available. Seek medical attention in the event of irritation.
Inhaled	Remove to fresh air. Encourage the patient to clear nasal passages by blowing nose. Rinse mouth with water and consider drinking to clear throat. Seek medical attention. If breathing has stopped, ensure the airway is clear and apply resuscitation. Transport to hospital or doctor.
Advice To Doctor	Treat symptomatically.

PRECAUTIONS FOR USE	
Exposure Standards	Chrome, elemental and inorganic compounds as Cr
	TLV TWA 0.05 mg/m3 as dust
	ACGIH = American Conference of Governmental Industrial Hygienists.
	TWA = Time Weighted Average
	NOHSC =National Health & Safety Commission
Engineering Controls	Ensure workplace is well ventilated.
Personal Protection	Approved respirator to AS1715 to be worn, gloves, safety glasses and protective overalls. Wash hands and face
	thoroughly after handling and before work breaks, eating, drinking, smoking and using toilet facilities.
Flammability	Not flammable under the conditions of use but the containers may burn.

SAFE HANDLING INFORMATION	
Storage & Transport	Store and transport in accordance with all regulations. Keep tightly closed in a dry, cool and well-ventilated
	place. Not subject to hazardous substances labelling.
Spills & Disposal	Dispose of in accordance with all Local, State and Federal regulations by incineration or disposal to landfill.
Fire / Explosion Hazard	Fire-fighters should wear full protective clothing including self-contained breathing apparatus. Use water, foam or dry extinguishing media. Use equipment/media appropriate to surrounding fire conditions. Dispose of fire debris and contaminated extinguishing water in accordance with local regulations.

OTHER INFORMATION	
	AUSTRALIAN POISONS INFORMATION CENTRE
	24 HOUR SERVICE 13 11 26
	POLICE / FIRE / AMBULANCE 000

CONTACT POINT	Walker Ceramics 5 McLellan St, Bayswater, Victoria 3153, Australia
	Telephone (03) 8761 6322 Fax (03) 8761 6344
	Email sales@walkerceramics.com.au Website www.walkerceramics.com.au
	Date Of Issue: March 2019

This MSDS summarises, at the date of issue, our best knowledge of the health & safety hazard information for this product, and in particular how to safely handle and use this product in the workplace. Since Walker Ceramics and its agents cannot anticipate or control the conditions under which this product may be used, each user must prior to usage, review this MSDS in the context of how the user intends to handle and use this product in the workplace.

If clarification or further information is needed to ensure that an appropriate assessment can be made, the user should contact us.

Our responsibility for products sold, is subject to our standard terms and conditions, a copy of which is sent to our customers and is also available upon request.