



Clays Glazes Colours

Material Safety Data Sheet

BA200 Ball Clay FX/CA1

Company Details	Walker Ceramics 5 McLellan St, Bayswater, Victoria 3153, Australia Telephone (03) 8761 6322 Fax (03) 8761 6344 Email sales@walkerceramics.com.au Website www.walkerceramics.com.au Date Of Issue: March 2019
-----------------	---

IDENTIFICATION	
Product Name	Ball Clay FX/CA1
Other Names	None
Manufacturers Product Code	BA200
UN Number	None
Dangerous Goods Class & Subsidiary Code	None
Hazchem Code	None
Poisons Schedule Number	None
Use(s)	Used in ceramics and pottery.

PHYSICAL DESCRIPTION / PROPERTIES	
Appearance	Fine off white powder with clay odour when moistened.
Boiling Point / Melting Point	Not applicable
Vapour Pressure	Not applicable
Specific Gravity	Approx 2.7
Flashpoint	Not applicable
Flammability Limits	Not applicable
Solubility in Water	Immiscible
Other Properties	Very inert

INGREDIENTS		
Chemical Name	CAS Number	Proportion (%)
Kaolin as clay	1332-58-7	>60
Illite	68476-25-5	<10
Feldspars	68476-25-5	<10

HEALTH HAZARD INFORMATION	
Acute	Dust may cause irritation of the eyes, skin and respiratory tract. Prolonged and/or repeated exposure to the dust may result in fibrotic lung damage in some people.
Swallowed	Large doses may cause gastro-intestinal irritation.
Eye	The dust may cause irritation of the eyes.
Skin	The dust may cause irritation and dryness of the skin.
Inhaled	Breathing the dust may cause respiratory irritation and discomfort
Chronic	Repeated or prolonged exposure to dust may result in lung disease. Symptoms are those of nodular fibrosis and respiratory impairment is characterised by obstruction and restriction of lung function.

FIRST AID	
Swallowed	DO NOT INDUCE VOMITING. Give water or milk. Seek medical advice.
Eye	Immediately hold eyes open and wash continuously with running water for at least 15 minutes. Ensure irrigation includes under eyelids. TRAINED STAFF ONLY ARE TO ATTEMPT THE REMOVAL OF CONTACT LENSES. Seek medical attention without delay.
Skin	Wash thoroughly with soap and water. Change into clean clothing and launder contaminated clothing.
Inhaled	Remove to fresh air. If breathing has stopped apply artificial respiration and seek immediate medical assistance.
First Aid Facilities	Washing area, eye wash.
Advice To Doctor	Treat symptomatically.

PRECAUTIONS FOR USE	
Exposure Standards	Kaolin as clay TLV TWA 2.0 MG/M3 Illite TLV TWA 10.0 MG/M3 Feldspars TLV TWA 10.0 MG/M3 ACGIH = American Conference of Governmental Industrial Hygienists. TWA = Time Weighted Average NOHSC =National Health & Safety Commission
Engineering Controls	Ensure workplace is well ventilated.
Personal Protection	Approved respirator to AS1715 to be worn, gloves, safety glasses and protective overalls. Wash hands and face thoroughly after handling and before work breaks, eating, drinking, smoking and using toilet facilities.
Flammability	Not flammable under the conditions of use but the containers may burn.

SAFE HANDLING INFORMATION	
Storage & Transport	Store and transport in accordance with all regulations. Keep tightly closed in a dry, cool and well-ventilated place. Not subject to hazardous substances labelling.
Spills & Disposal	Dispose of in accordance with all Local, State and Federal regulations by incineration or disposal to landfill.
Fire / Explosion Hazard	Fire-fighters should wear full protective clothing including self-contained breathing apparatus. Use water, foam or dry extinguishing media. Use equipment/media appropriate to surrounding fire conditions. Dispose of fire debris and contaminated extinguishing water in accordance with local regulations.

OTHER INFORMATION	
	<u>AUSTRALIAN POISONS INFORMATION CENTRE</u> 24 HOUR SERVICE 13 11 26 POLICE / FIRE / AMBULANCE 000

CONTACT POINT	
	Walker Ceramics 5 McLellan St, Bayswater, Victoria 3153, Australia Telephone (03) 8761 6322 Fax (03) 8761 6344 Email sales@walkerceramics.com.au Website www.walkerceramics.com.au Date Of Issue: March 2019

This MSDS summarises, at the date of issue, our best knowledge of the health & safety hazard information for this product, and in particular how to safely handle and use this product in the workplace. Since Walker Ceramics and its agents cannot anticipate or control the conditions under which this product may be used, each user must prior to usage, review this MSDS in the context of how the user intends to handle and use this product in the workplace.

If clarification or further information is needed to ensure that an appropriate assessment can be made, the user should contact us.

Our responsibility for products sold, is subject to our standard terms and conditions, a copy of which is sent to our customers and is also available upon request.