BA340 feldspar soda



Material Safety Data Sheet

BA340 Feldspar Soda

Clays Glazes Colours

Company Details Walker Ceramics 5 McLellan St, Bayswater, Victoria 3153, Australia Telephone (03) 8761 6322 Fax (03) 8761 6344 Email <u>sales@walkerceramics.com.au</u> Website <u>www.walkerceramics.com.au</u> Date Of Issue: March 2019

IDENTIFICATION	
Product Name	Feldspar Soda
Other Names	None
Manufacturers Product Code	BA340
UN Number	None
Dangerous Goods Class & Subsidiary Code	None
Hazchem Code	None
Poisons Schedule Number	None
Use(s)	Used in pottery and ceramics.

PHYSICAL DESCRIPTION / PROPERTIES		
Appearance	Fine off white powder darkens to a clay colour when moistened.	
Boiling Point / Melting Point	Not applicable	
Vapour Pressure	Not applicable	
Specific Gravity	Approx 2.7	
Flashpoint	Not applicable	
Flammability Limits	Not applicable	
Solubility in Water	Negligible	
Other Properties	Very inert	

INGREDIENTS

Chemical Name	CAS Number	Proportion (%)
Feldspars as soda feldspars	68476-25-5	>98

HEALTH HAZA	ARD INFORMATION
Acute	Dust may cause irritation of the eyes, skin and respiratory tract. Prolonged and/or repeated exposure to the dust may result in
	fibrotic lung damage (silicosis) in some people.
Swallowed	Large doses may cause gastro-intestinal irritation.
Eye	The dust may cause irritation of the eyes.
Skin	The dust may cause irritation and dryness of the skin.
Inhaled	Breathing the dust may cause respiratory irritation and discomfort
Chronic	The principal route of exposure is via the inhalation of the dust. Chronic dust inhalation has been associated with lung disease (source NIOSHTIC). Symptoms are those of nodular fibrosis and respiratory impairment is characterised by obstruction and
	restriction of lung function.

FIRST AID	
Swallowed	DO NOT INDUCE VOMITING. If conscious, give water or milk. Provide liquid slowly. Seek medical advice.
Eye	Irrigate with water for at least 15 minutes including eyelids and seek medical advice if symptoms persist.
Skin	Wash thoroughly with soap and water. Change into clean clothing and launder contaminated clothing.
Inhaled	Remove to fresh air and keep warm and rested. If breathing has stopped apply artificial respiration and seek immediate medical assistance.
First Aid Facilities	Washing area, eye wash.
Advice To Doctor	Treat symptomatically.

PRECAUTIONS FOR USE	
Exposure Standards	Feldspars
	TLV TWA 10 mg/m3 as dust
	Silica as Quartz
	TLV TWA 0.1 mg/m3 (respirable dust)
	ACGIH = American Conference of Governmental Industrial Hygienists.
	TWA = Time Weighted Average
	NOHSC =National Health & Safety Commission
Engineering Controls	Ensure workplace is well ventilated.
Personal Protection	Approved respirator to AS1715 to be worn, gloves, safety glasses and protective overalls. Wash hands and face
	thoroughly after handling and before work breaks, eating, drinking, smoking and using toilet facilities.
Flammability	Not flammable under the conditions of use but the containers may burn.

SAFE HANDLING INFORMATION	
Storage & Transport	Store and transport in accordance with all regulations. Keep tightly closed in a dry, cool and well-ventilated place. Not subject to hazardous substances labelling.
Spills & Disposal	Dispose of in accordance with all Local, State and Federal regulations by incineration or disposal to landfill.
Fire / Explosion Hazard	Fire-fighters should wear full protective clothing including self-contained breathing apparatus. Use water, foam or dry extinguishing media. Use equipment/media appropriate to surrounding fire conditions. Dispose of fire debris and contaminated extinguishing water in accordance with local regulations.

OTHER INFORMATION	AUSTRALIAN POISONS INFORMATION CENTRE 24 HOUR SERVICE 13 11 26 POLICE / FIRE / AMBULANCE 000
CONTACT POINT	Walker Ceramics 5 McLellan St, Bayswater, Victoria 3153, Australia Telephone (03) 8761 6322 Fax (03) 8761 6344 Email <u>sales@walkerceramics.com.au</u> Website <u>www.walkerceramics.com.au</u> Date Of Issue: March 2019

This MSDS summarises, at the date of issue, our best knowledge of the health & safety hazard information for this product, and in particular how to safely handle and use this product in the workplace. Since Walker Ceramics and its agents cannot anticipate or control the conditions under which this product may be used, each user must prior to usage, review this MSDS in the context of how the user intends to handle and use this product in the workplace.

If clarification or further information is needed to ensure that an appropriate assessment can be made, the user should contact us.

Our responsibility for products sold, is subject to our standard terms and conditions, a copy of which is sent to our customers and is also available upon request.