

Material Safety Data Sheet



Clays Glazes Colours

BA850 Talc

Company Details	Walker Ceramics 5 McLellan Street Bayswater Victoria 3153, Australia Telephone (03) 8761 6322 Fax (03) 8761 6344 Email sales@walkerceramics.com.au Website www.walkerceramics.com.au Date Of Issue: March 2019
------------------------	---

IDENTIFICATION	
Product Name	Talc
Other Names	None
Manufacturers Product Code	BA850
UN Number	None
Dangerous Goods Class & Subsidiary Code	None
Hazchem Code	None
Poisons Schedule Number	None
Use(s)	Used in ceramics and pottery.

PHYSICAL DESCRIPTION / PROPERTIES	
Appearance	Fine odourless off white powder with a pearl lustre and greasy feel..
Boiling Point / Melting Point	Not available
Vapour Pressure	Not applicable
Specific Gravity	3.0
Flashpoint	Not applicable
Flammability Limits	Not applicable
Solubility in Water	Immiscible.
Other Properties	High resistance to acids, alkalis and heat.

INGREDIENTS		
Chemical Name	CAS Number	Proportion (%)
Talc	14807-96-6	100

HEALTH HAZARD INFORMATION	
Acute	
Swallowed	This material is considered non-toxic but may be mildly discomforting if swallowed.
Eye	The dust may produce eye discomfort and abrasive eye inflammation.
Skin	This product may cause dryness. Open cuts, abraded or irritated skin should not be exposed to this material. It may accentuate any pre-existing skin condition.
Inhaled	This product as dust may be discomforting and irritating to the upper respiratory tract but may present a hazard from repeated or prolonged exposure.
Chronic	The principle route of exposure is via inhalation. Though considered non-harmful, slight irritation may result from contact because of the abrasive nature of the product. Prolonged exposure to the skin may lead to coughing, wheezing, difficulty breathing with lung impairment. Prolonged exposure may result in dryness & cracking of the skin and possible dermatitis.

FIRST AID	
Swallowed	DO NOT INDUCE VOMITING. If conscious, give water or milk to rinse out mouth and then drink. Provide liquid slowly but as much as the patient will drink. Transport to hospital without delay.
Eye	Immediately hold eyes open and wash continuously with running water for at least 15 minutes. Ensure irrigation includes under eyelids. TRAINED STAFF ONLY ARE TO ATTEMPT THE REMOVAL OF CONTACT LENSES. Seek medical attention without delay.
Skin	Wash affected areas thoroughly with soap and water if available. Seek medical attention in the event of irritation.
Inhaled	If fumes or combustion products are inhaled: Remove to fresh air. Encourage the patient to clear nasal passages by blowing nose. Rinse mouth with water and consider drinking to clear throat. Seek medical attention. If breathing has stopped, ensure the airway is clear and apply resuscitation. Transport to hospital or doctor.
Advice To Doctor	Treat symptomatically.

PRECAUTIONS FOR USE	
Exposure Standards	Talc containing no asbestos fibre TLV TWA 2.0 mg/m ³ as dust ACGIH = American Conference of Governmental Industrial Hygienists. TWA = Time Weighted Average NOHSC =National Health & Safety Commission
Engineering Controls	Ensure workplace is well ventilated.
Personal Protection	Approved respirator to AS1715 to be worn, gloves, safety glasses and protective overalls. Wash hands and face thoroughly after handling and before work breaks, eating, drinking, smoking and using toilet facilities.
Flammability	Not flammable under the conditions of use but the containers may burn.

SAFE HANDLING INFORMATION	
Storage & Transport	Store and transport in accordance with all regulations. Keep tightly closed in a dry, cool and well-ventilated place. Not subject to hazardous substances labelling.
Spills & Disposal	Dispose of in accordance with all Local, State and Federal regulations by incineration or disposal to landfill.
Fire / Explosion Hazard	Fire-fighters should wear full protective clothing including self-contained breathing apparatus. Use water, foam or dry extinguishing media. Use equipment/media appropriate to surrounding fire conditions. Dispose of fire debris and contaminated extinguishing water in accordance with local regulations.

OTHER INFORMATION	
<u>AUSTRALIAN POISONS INFORMATION CENTRE</u> 24 HOUR SERVICE 13 11 26 POLICE / FIRE / AMBULANCE 000	

CONTACT POINT	
Walker Ceramics 5 McLellan Street Bayswater Victoria 3153, Australia Telephone (03) 8761 6322 Fax (03) 8761 6344 Email sales@walkerceramics.com.au Website www.walkerceramics.com.au Date Of Issue: March 2019	

This MSDS summarises, at the date of issue, our best knowledge of the health & safety hazard information for this product, and in particular how to safely handle and use this product in the workplace. Since Walker Ceramics and its agents cannot anticipate or control the conditions under which this product may be used, each user must prior to usage, review this MSDS in the context of how the user intends to handle and use this product in the workplace.

If clarification or further information is needed to ensure that an appropriate assessment can be made, the user should contact us.

Our responsibility for products sold, is subject to our standard terms and conditions, a copy of which is sent to our customers and is also available upon request.