

Material Safety Data Sheet

ETP1 Diamond Pooling Glaze

Clays Glazes Colours

		s Hazardous According To Criteria Of S	are work rustrana.	
Company Details	Telephone (03) 8761 632 Email <u>sales@walkercera</u>	Walker Ceramics 5 McLellan Street Bayswater Victoria 3153, Australia Telephone (03) 8761 6322 Fax (03) 8761 6344 Email <u>sales@walkerceramics.com.au</u> Website <u>www.walkerceramics.com.au</u> Date Of Issue: March 2019		
IDENTIFICATIC)NI			
Product Name		Diamond Pooling Glaze		
Other Names		None		
Manufacturers Product Code		ETP1		
UN Number		None		
Dangerous Goo	ds Class & Subsidiary Code	None		
Hazchem Code		None		
Poisons Schedu	ile Number	None		
Use(s)		Used in the decoration of pottery & ceramics.		
PHYSICAL DESCRIPTION / PROPERTIES Appearance Boiling Point / Melting Point Vapour Pressure Specific Gravity		Fine off white powder >300°C Not applicable Approx 2.5		
Flashpoint		Not applicable		
Flammability Limits		Not applicable		
Solubility in Water		Negligible		
Other Properties			materials, colouring oxides and small amounts of d mixture of inorganic substances in the form of	
INGREDIENTS		CAS Number	Proportion (%)	
	Chemical Name	CAS Number 65997-18-4	Proportion (%)	
		CAS Number 65997-18-4 1332-58-7	Proportion (%) >60 <30	

HEALTH HA	
Acute	The hazardous ingredients for this product is incorporated into the glass like structure of the frit, chemically reacted in the form of silicates or other essentially insoluble complexes. Exposure to the hazardous ingredients can occur if the dust is inhaled or ingested and the ingredients dissolve out. This process is anticipated to occur very slowly. Dust may cause irritation of the eyes, skin and respiratory tract. Prolonged and/or repeated exposure to the dust may result in fibrotic lung damage (silicosis) in some people. Borax is considered hazardous because of its irritating effects on the eyes, nose & throat Nuisance particulates can cause unpleasant or uncomfortable deposits in the eyes, ears & nose but do not cause any toxic effect when exposures are kept in reasonable control.
Swallowed	Large doses may cause gastro-intestinal irritation.
Eye	The dust may cause irritation of the eyes.
Skin	The dust may cause irritation and dryness of the skin.
Inhaled	Breathing the dust may cause respiratory irritation and discomfort
Chronic	No specific information is available.

FIRST AID	
Swallowed	Give water or milk. Seek medical advice.
Eye	Irrigate with water for at least 15 minutes and seek medical advice if symptoms persist.
Skin	Wash thoroughly with soap and water. Change into clean clothing and launder contaminated clothing.
Inhaled	Remove to fresh air. If breathing has stopped apply artificial respiration and seek immediate medical assistance.
First Aid Facilities	Washing area, eye wash.
Advice To Doctor	Treat symptomatically.

PRECAUTIONS FOR USE **Exposure Standards** CAS# 14808-60-7 Silica, crystalline, Quartz NOHSC TWA: 0.1 mg/m3 (respirable dust) CAS# 7440-67-2 Borax, anhydrous and pentahydrate NOHSC TWA: 1.0 mg/m3 CAS# 1332-58-7 Kaolin NOHSC TWA: 10.0 mg/m3 CAS# Various Nuisance dusts, various NOHSC TWA: 10.0 mg/m3 ACGIH = American Conference of Governmental Industrial Hygienists. TWA = Time Weighted Average NOHSC =National Health & Safety Commission **Engineering Controls** Ensure workplace is well ventilated. Personal Protection Approved respirator to AS1715 to be worn, gloves, safety glasses and protective overalls. Wash hands and face thoroughly after handling and before work breaks, eating, drinking, smoking and using toilet facilities. Flammability Not flammable under the conditions of use but the containers may burn.

SAFE HANDLING INFORMATION

Storage & Transport	Store and transport in accordance with all regulations. Keep tightly closed in a dry, cool and well-ventilated
	place. Not subject to hazardous substances labelling.
Spills & Disposal	Dispose of in accordance with all Local, State and Federal regulations by incineration or disposal to landfill.
Fire / Explosion Hazard	Fire-fighters should wear full protective clothing including self-contained breathing apparatus. Use water,
	foam or dry extinguishing media. Use equipment/media appropriate to surrounding fire conditions. Dispose of
	fire debris and contaminated extinguishing water in accordance with local regulations.

OTHER INFORMATION	AUSTRALIAN POISONS INFORMATION CENTRE 24 HOUR SERVICE 13 11 26 POLICE / FIRE / AMBULANCE 000
CONTACT POINT	Walker Ceramics 5 McLellan Street Bayswater Victoria 3153, Australia Telephone (03) 8761 6322 Fax (03) 8761 6344 Email <u>sales@walkerceramics.com.au</u> Website <u>www.walkerceramics.com.au</u> Date Of Issue: March 2019

This MSDS summarises, at the date of issue, our best knowledge of the health & safety hazard information for this product, and in particular how to safely handle and use this product in the workplace. Since Walker Ceramics and its agents cannot anticipate or control the conditions under which this product may be used, each user must prior to usage, review this MSDS in the context of how the user intends to handle and use this product in the workplace.

If clarification or further information is needed to ensure that an appropriate assessment can be made, the user should contact us.

Our responsibility for products sold, is subject to our standard terms and conditions, a copy of which is sent to our customers and is also available upon request.