WALKER Ceramics

Material Safety Data Sheet

ETQ6132 Egyptian Blue Crackle Glaze

Clays Glazes Colours

	Not classified as	Hazardous According To Criteria Of Safe V	Vork Australia.	
Company Details	Walker Ceramics 5 McLellan Street Bayswater Victoria 3153, Australia Telephone (03) 8761 6322 Fax (03) 8761 6344 Email <u>sales@walkerceramics.com.au</u> Website <u>www.walkerceramics.com.au</u> Date Of Issue: March 2019			
IDENTIFICAT	TION			
Product Name		Egyptian Blue Crackle Glaze		
Other Names		ETQ6132		
Manufacturers Product Code		ETQ6132		
UN Number		None		
Dangerous G	oods Class & Subsidiary Code	None		
Hazchem Coo		None		
Poisons Sche	edule Number	None		
Use(s)		Used in the decoration of pottery & ceramics.		
PHYSICAL D	ESCRIPTION / PROPERTIES			
Appearance		Light Blue powder.		
Boiling Point	/ Melting Point	>300°C		
Vapour Press	sure	Not applicable		
Specific Grav	ity	1.2-1.5		
Flashpoint		Not applicable		
Flammability		Not applicable		
Solubility in W		Negligible		
Other Propert	ties	Glazes are essentially mixtures formed by blending frit powders, clays and other raw materials.		
INGREDIENT	S			
	Chemical Name	CAS Number	Proportion (%)	
	Frits, chemical	65997-18-4	>60	
	Silica (Quartz)	14808-60-7	<30	
	pper (II) Carbonate basic	12069-69-1	<5	
Co	balt (II) carbonate basic	12602-23-2	<5	
	Kaolin as clay	1332-58-7	<5	
HEALTH HAZ				
Acute	The silica for this product is incorporated into the glass like structure of the frit, chemically reacted in the form of silicates or other essentially insoluble complexes. Exposure to the hazardous ingredients can occur if the dust is inhaled or ingested and the ingredients dissolve out. This process is anticipated to occur very slowly. Dust may cause irritation of the eyes, skin and respiratory tract. Prolonged and/or repeated exposure to the dust may result in fibrotic lung damage (silicosis) in some people.			
Swallowed	Large doses may cause gastro-intestinal irritation.			
Eye	The dust may cause irritation of the eyes.			
Skin	The dust may cause irritation and dryness of the skin.			
Inhaled	Breathing the dust may cause respiratory irritation and discomfort			
Chronic	No specific information is avail			

FIRST AID	
Swallowed	Give water or milk. Seek medical advice.
Eye	Irrigate with water for at least 15 minutes and seek medical advice if symptoms persist.
Skin	Wash thoroughly with soap and water. Change into clean clothing and launder contaminated clothing.
Inhaled	Remove to fresh air. If breathing has stopped apply artificial respiration and seek immediate medical assistance.
First Aid Facilities	Washing area, eye wash.
Advice To Doctor	Treat symptomatically.

PRECAUTIONS FOR USE

Exposure Standards	CAS# 7440-67-2 Borax, anhydrous and pentahydrate NOHSC TWA: 1.0 mg/m3
	Silica (as respirable dust) ACGHI 0.01 mg/m3
	Copper as dust TLV_TWA 0.02 mg/m3
	Cobalt as Co TLV TWA 0.02 mg/m3
	Kaolin as clay
	TLV TWA 2.0 mg/m3
	ACGIH = American Conference of Governmental Industrial Hygienists.
	TWA = Time Weighted Average NOHSC =National Health & Safety Commission
Engineering Controls	Ensure workplace is well ventilated.
Personal Protection	Approved respirator to AS1715 to be worn, gloves, safety glasses and protective overalls. Wash hands and face thoroughly after handling and before work breaks, eating, drinking, smoking and using toilet facilities.
Flammability	Not flammable under the conditions of use but the containers may burn.

SAFE HANDLING INFORMATION

Storage & Transport	Store and transport in accordance with all regulations. Keep tightly closed in a dry, cool and well-ventilated
	place. Not subject to hazardous substances labelling.
Spills & Disposal	Dispose of in accordance with all Local, State and Federal regulations by incineration or disposal to landfill.
Fire / Explosion Hazard	Fire-fighters should wear full protective clothing including self-contained breathing apparatus. Use water,
	foam or dry extinguishing media. Use equipment/media appropriate to surrounding fire conditions. Dispose
	of fire debris and contaminated extinguishing water in accordance with local regulations.

OTHER INFORMATION	AUSTRALIAN POISONS INFORMATION CENTRE 24 HOUR SERVICE 13 11 26 POLICE / FIRE / AMBULANCE 000
CONTACT POINT	Walker Ceramics 5 McLellan Street Bayswater Victoria 3153, Australia Telephone (03) 8761 6322 Fax (03) 8761 6344 Email <u>sales@walkerceramics.com.au</u> Website <u>www.walkerceramics.com.au</u> Date Of Issue: March 2019

This MSDS summarises, at the date of issue, our best knowledge of the health & safety hazard information for this product, and in particular how to safely handle and use this product in the workplace. Since Walker Ceramics and its agents cannot anticipate or control the conditions under which this product may be used, each user must prior to usage, review this MSDS in the context of how the user intends to handle and use this product in the workplace. If clarification or further information is needed to ensure that an appropriate assessment can be made, the user should contact us.

Our responsibility for products sold, is subject to our standard terms and conditions, a copy of which is sent to our customers and is also available upon request.