

Clays Glazes Colours

Material Safety Data Sheet

FK2 Tropical Lime Design Colour

Not classified as Hazardous According To Criteria Of Safe Work Australia.		
Details Telephone (03) 8761 6322	cs.com.au Website www.walkerceramics.com.a	<u>u</u>
IDENTIFICATION		
Product Name	Tropical Lime Design Colour Liquid Concentrate	
ther Names None		
Manufacturers Product Code	FK2	
UN Number	N/A	
Dangerous Goods Class & Subsidiary Code	N/A	
Hazchem Code	N/A	
Poisons Schedule Number	N/A	
Use(s)	Decoration of ceramic & pottery ware.	
	l	
PHYSICAL DESCRIPTION / PROPERTIES	Ore estate de ser l'autit	
Appearance	Greenish viscose liquid.	
Boiling Point / Melting Point	197°C+	
Vapour Pressure	< 1mm of Hg	
Specific Gravity	1.2-1.4	
Flashpoint	Not applicable	
Flammability Limits	Non-flammable.	
Solubility in Water	Not applicable	
Other Properties	Miscible with water, alcohol and ether. Ceramic stains or pigments are formed by	
	high temperature calcination and silica or f	eldspar.
INGREDIENTS		
Chemical Name	CAS Number	Proportion (%)
Silica	14808-60-7	<10
Red Inclusion Pigment	Common Name	<10
Clyerine	56-81-5	<5
Copper (II) Carbonate basic	12069-69-1	<1
Ingredients determined not to be hazardous		Up to 100
HEALTH HAZARD INFORMATION		
Acute		- Linder Con
Swallowed	Large oral doses may cause gastrointestinal irritation.	
Eye	Dust may cause irritation to eyes.	
Skin	Dust may cause irritation and dryness of the skin.	

 Skin
 Dust may cause irritation and dryness of the skin.

 Inhaled
 Breathing dust may cause respiratory irritation and discomfort.

 Chronic
 Silica dust may cause mechanical irritation of the eyes, skin & respiratory tract.

 Prolonged exposure to crystalline silica dust can result in silicosis in some people.

FIRST AID		
Swallowed	Rinse mouth and then drink plenty of water in small sips.	
Eye	Wash affected eyes for at least 15 minutes under running water with eyelids held	
y -	open. Seek medical attention if irritation persists.	
Skin	Wash thoroughly with soap and water.	
Inhaled	Keep patient calm and remove to fresh air.	
First Aid Facilities	Ensure an eye bath is available and ready for use.	
Advice To Doctor	Treat symptomatically based on judgement of doctor and individual reactions of patient.	
PRECAUTIONS FOR USE		
Exposure Standards	Silica TWA 0.1mg/m3 as respirable dust.	
	Ceramic stain with Cadmium &Zircon	
	0.150 mg/m3 as dust referring to compounds AGCHI TWA	
	Clycerine 10 mg/m3 ACGIH TWA as vapour	
	Elemental & Inorganic Compounds Copper (II) Carbonate TLV TWA 0.02 mg/m3	
	ACGIH = American Conference of Governmental Industrial Hygienists. TWA = Time Weighted Average	
For vice a vice of October la	NOHSC =National Health & Safety Commission	
Engineering Controls	Ensure workplace is well ventilated.	
Personal Protection	Protective clothing. Wash hands and face thoroughly after handling and before work breaks, eating, drinking, smoking and using toilet facilities.	
Flammability	Not applicable	
SAFE HANDLING INFORMATION		
Storage & Transport	Store and transport in accordance with all regulations. Keep tightly closed in a dry, cool and well-ventilated place. Not subject to hazardous substances labelling.	
Spills & Disposal	Dispose of in accordance with all Local, State and Federal regulations by incineration or disposal to landfill.	
Fire / Explosion Hazard	Fire-fighters should wear full protective clothing including self-contained breathing apparatus. Use water, foam or dry extinguishing media. Use equipment/media appropriate to surrounding fire conditions. Dispose of fire debris and contaminated extinguishing water in accordance with local regulations.	
OTHER INFORMATION	Ecotoxic effects : no data available	
CONTACT POINT	Walker Ceramics 5 McLellan Street Bayswater Victoria 3153, Australia Telephone (03) 8761 6322 Fax (03) 8761 6344 Email <u>sales@walkerceramics.com.au</u> Website <u>www.walkerceramics.com.au</u> Date Of Issue: March 2019	

This MSDS summarises, at the date of issue, our best knowledge of the health & safety hazard information for this product, and in particular how to safely handle and use this product in the workplace. Since Walker Ceramics Ltd and its agents cannot anticipate or control the conditions under which this product may be used, each user must prior to usage, review this MSDS in the context of how the user intends to handle and use this product in the workplace.

If clarification or further information is needed to ensure that an appropriate assessment can be made, the user should contact us.

Our responsibility for products sold, is subject to our standard terms and conditions, a copy of which is sent to our customers and is also available upon request.