MATERIAL SAFETY DATA SHEET

Walker Ceramics 5 McLellan Street Bayswater Victoria 3153, Australia Telephone (03) 8761 6322 Fax (03) 8761 6344 Email sales@walkerceramics.com.au Website www.walkerceramics.com.au

FQ8 Brick Red Underglaze

Date Of Issue: March 2019

Not classified as Hazardous According To Criteria Of Safe Work Australia.

IDENTIFICATION

Product name:	Cesco TM Brush-on Underglaze	Cesco [™] Brush-on Und
Code:	FQ8 Brick Red Underglaze	FQ8 Brick Red Undergl

COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS number	Proportion
Chemical Name		
Zirconium-cadmium selenide/sulfide-	102184-95-2	>60%
silicate inclusion colour		
Frit	65997-18-4	<10%

Ceramic stains are blended mixtures of pigments formed by high calcination with silica &/or feldspar. The cadmium pigment is encapsulated in Zircon, rendering it stable at high temperatures. This also reduces the hazards associated with the cadmium compound, but does not eliminate them. This cadmium stain also contains Barium.

Frit is a chemically reacted mixture of inorganic substances in the form of essentially insoluble glassy silicates.

Underglazes are milled mixtures of ceramic stains and small amounts of milling additives, for application on ceramic surfaces under transparent glaze.

PHYSICAL DESCRIPTION/PROPERTIES

Red viscous liquid Negligible Not applicable >400° C.
Not applicable
Approximately 5.0
Not applicable
Does not burn
Negligible

HEALTH HAZARD INFORMATION

Health effects: Acute	
Ingestion:	The product is of low solubility in body fluids and it is likely to be of low acute toxicity.
Inhalation:	Excessive exposure may cause damage to the lungs and kidneys.
Eyes:	May cause physical irritation and inflammation.
Skin:	The material is not a primary irritant, but may give rise to minor irritation.

MATERIAL SAFETY DATA SHEET

Walker Ceramics 5 McLellan Street Bayswater Victoria 3153, Australia Telephone (03) 8761 6322 Fax (03) 8761 6344 Email sales@walkerceramics.com.au Website www.walkerceramics.com.au

FQ8 Brick Red Underglaze

Date Of Issue: March 2019

Chronic

Chronic Exposure:	Prolonged or repeated exposure above Occupational Exposure Standards may cause lung or kidney damage. Prolonged exposure to dust may lead to pulmonary problems.
First Aid Measures:	
Eye Contact	Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician if irritation persists.
Ingestion:	Rinse mouth. Do not induce vomiting. Seek medical advice.
Inhalation:	Move to fresh air. If breathing has stopped, apply artificial respiration and seek medical attention.
Claim agenta at	Weak off with soon and plants of water

Skin contact: Wash off with soap and plenty of water.

Advice to Doctor: Treat symptomatically.

PRECAUTIONS FOR USE

Exposure Standards

CAS 7440-39-3	Barium compounds (as Ba U.K. OELS TWA:	a) -less than 1% in product 0.5mg/cubic metre
CAS N/A	Cadmium pigments, respir U.K. OELS TWA	rable dust (as Cd) -less than 1% in product 0.03mg/cubic metre
CAS 7440-67-2	Zirconium compounds, (a NOHSC TWA: NOHSC STEL:	s Zr) 5.0mg/cubic metre 10.0mg/cubic metre
CAS 14808-60-7	Silica, crystalline, Quartz NOHSC TWA:	0.2mg/cubic metre
CAS 1303-96-4	Borax, anhydrous & penta NOHSC TWA:	hydrate 1.0 mb/cubic metre

Pigments are formed by high temperature calcination. Therefore, they do not necessarily have any of the properties of their component oxides or metals.

Frit is produced by rapidly quenching a molten mixture of inorganic substances in glassy form from high temperature, thereby confining the substances into the frit as chemically reacted non-migratory components in the form of silicates or other essentially insoluble substances.

Personal protection

VENTILATION:	Use local exhaust ventilation to keep air contaminants below their TWAs
PERSONAL PROTECTION:	Safety glasses/goggles Cotton work gloves Apron or overalls Face mask or respirator conforming to AS1715 for dust

MATERIAL SAFETY DATA SHEET

Walker Ceramics 5 McLellan Street Bayswater Victoria 3153, Australia Telephone (03) 8761 6322 Fax (03) 8761 6344 Email sales@walkerceramics.com.au Website www.walkerceramics.com.au

FQ8 Brick Red Underglaze

Date Of Issue: March 2019

SAFE HANDLING INFORMATION

Accidental release measures

Clean up/Disposal:	For small spills or leaks, use suitable vacuum equipment otherwise damp down and scoop into receptacle For large spills pick up as much as possible and dispose of in closed containers, wash the remainder with plenty of water.
Personal Protection:	Wear apron or overalls, rubber gloves, chemical goggles or safety glasses and respiratory protective equipment.
Handling and storage	Do not eat, drink, or smoke in areas where material is used. Wash thoroughly after handling. Keep lids on containers tightly closed. Store away from consumables.

FIRE/EXPLOSION HAZARD

Fire Fighting Measures

Extinguishing media: Suitable for surrounding fir contidons. Special exposure hazard: In the event of fire the product may emit harmful or toxic fumes. No limitations for fighting surrounding fire.

TRANSPORT INFORMATION

This product is not classified for transport as a dangerous good as defined in the ADG Code or the IMDG code.

REGULATORY INFORMATION

EC Supply labelling:	Harmful Xn
R-Phrases:	R20/22 Harmful by inhalation and if swallowe.
R33	Danger of cumulative effects.
S-Phrases:	S13 Keep away from food, drink and animal feeding stuffs.
S20/21	When using do not eat, drink or smoke.
S22	Do not breathe dust
S23	Do not breath spray.
S28	After contact with skin, wash immediately with plenty of water.

Walker Ceramics 5 McLellan Street Bayswater Victoria 3153, Australia Telephone (03) 8761 6322 Fax (03) 8761 6344 Email <u>sales@walkerceramics.com.au</u> Website <u>www.walkerceramics.com.au</u>

The information contained in this Safety Data Sheet is correct to the best of our knowledge at the date of publication and whilst every care has been exercised in the preparation, Walker Ceramics accepts no responsibility for any use which may be made of the contents.