

Material Safety Data Sheet FW5674 Intense Black Stain

Clays Glazes Colours

This substance is not classified as hazardous according to criteria of Worksafe Australia.

Company Details Walker Ceramics 5 McLellan Street Bayswater Victoria 3153, Australia

Telephone (03) 8761 6322 Fax (03) 8761 6344

Email sales@walkerceramics.com.au Website www.walkerceramics.com.au

Date Of Issue: March 2019

| IDENTIFICATION | |
|---|---------------------------------------|
| Product Name | Intense Black Stain |
| Other Names | None |
| Manufacturers Product Code | FW5674 |
| UN Number | N/A |
| Dangerous Goods Class & Subsidiary Code | N/A |
| Hazchem Code | N/A |
| Poisons Schedule Number | N/A |
| Use(s) | Decoration of ceramic & pottery ware. |

| PHYSICAL DESCRIPTION / PROPERTIES | |
|-----------------------------------|--|
| Appearance | Fine black powder. |
| Boiling Point / Melting Point | >400 C |
| Vapour Pressure | Not applicable |
| Specific Gravity | Not applicable |
| Flashpoint | Not applicable |
| Flammability Limits | Non-flammable. |
| Solubility in Water | Not applicable |
| Other Properties | This product is a mixture of various metal oxides, salts and some compounds, considered to |
| | be a nuisance dust, are interfused to form the final product, which does not represent |
| | individual components. |

| INGREDIENTS | | |
|-----------------------------|------------|----------------|
| Chemical Name | CAS Number | Proportion (%) |
| Iron Cohalt Chromite Spinel | 68186-97-0 | 100 |

| HEALTH HAZARD INFORMATION | |
|---------------------------|---|
| Acute | |
| Swallowed | Toxicity by this route is of a low order. |
| Eye | Dust may cause irritation to eyes. |
| Skin | Dust may cause irritation and dryness of the skin. |
| Inhaled | Breathing dust may cause respiratory irritation and disabling progressive pulmonary fibrosis due to the free quartz silica. |
| Chronic | Prolonged or repeated exposure may cause skin, mucous membrane and eye irritation. It may also cause iron deficiency. Chromium, Iron and their certain compounds are deemed a possible cancer hazard. Long-term exposure to silica dust can cause silicosis, which is characterized by shortness of breath, coughing, chest discomfort. Elemental manganese fumes and dust, when in high concentration may cause damage to the central nervous system with symptoms including sleepiness, weakness, emotional disturbances, spastic gait, mash-like facial expressions and paralysis. |

| FIRST AID | |
|----------------------|---|
| Swallowed | Rinse mouth. Do not induce vomiting. Consult doctor. |
| Eye | Wash affected eyes for at least 15 minutes under running water with eyelids held open. |
| | Seek medical attention if irritation persists. |
| Skin | Remove contaminated clothing. Wash thoroughly with soap and water. |
| Inhaled | Keep patient calm and remove to fresh air. Give oxygen if necessary. |
| First Aid Facilities | Ensure an eye bath is available and ready for use. |
| Advice To Doctor | Treat symptomatically based on judgement of doctor and individual reactions of patient. |

| PRECAUTIONS FOR USE | |
|----------------------|---|
| Exposure Standards | |
| CAS# 7440-47-3 | Chrome Oxide as Chrome (as Cr) |
| | NOHSC TWA 0.5 mg/m3 |
| 0.10 7.140 40 4 | Cobalt Metal, dust and fume, (as Co) |
| CAS# 7440-48-4 | NOHSC TWA 0.05 mg/m3 (Sensitiser) |
| | Notice TWA 6.66 Highlia (octionast) |
| CAS# 7440-02-0 | Nickel, Metal and insoluble compounds (as Ni) |
| 0/10// 1440 02 0 | NOHSC TWA 1.0 mg/m3 (Sensitiser) |
| | |
| CAS# 7439-96-5 | Manganese Compounds as Manganese |
| | NOHSC TWA 1.0 mg/m3 |
| | Nuisance Dusts |
| CAS# Not Listed | NOHSC TWA: 10.0 mg/m3 (Inspirable dust) |
| | |
| | Pigments are formed by high temperature calcinations. Therefore, they do not necessarily |
| | have any of the properties of their component oxides or metals. |
| | TWA = Time Weighted Average |
| | NOHSC =National Health & Safety Commission |
| Engineering Controls | Ensure workplace is well ventilated. |
| Personal Protection | Respiratory Protection: A particulate respirator Class P2 conforming to AS1716 suitable for |
| | dust should be worn |
| | when this material is being used. |
| | Protective Gloves: Cotton work gloves should be worn. |
| | Eye Protection: Wear general use industrial goggles or safety glasses. |
| | Clothing: Clean full-length overalls should be worn. |
| F1 129 | Safety Boots: Safety boots should be worn. |
| Flammability | Not applicable |

| SAFE HANDLING INFORMATION | |
|---------------------------|--|
| Storage & Transport | No special transport requirements are necessary. Store in a cool, dry, well ventilated area away from food, drink and animal feeding stuffs. Wear personal protective equipment and wash thoroughly after handling. Containers are to be kept closed when not in use to avoid generating dusts and minimise contamination. |
| Spills & Disposal | Transfer material via scoop or vacuum to closed containers for re-use or disposal. Minimise the generation of dusts. Wear apron, rubber gloves, chemical goggles or safety glasses. Wash clothes before re-use. No special environmental precautions required. Disposal should be in accordance with local, state, and federal regulations. |
| Fire / Explosion Hazard | FLAMMABILITY: Not Flammable. Fire/Explosion Hazard: Material is not combustible and will not burn in a fire. Extinguishing Media: Use water spray, dry chemical, CO2, or foam as required for fighting surrounding fire HAZCHEM CODE: None allocated |

| OTHER INFORMATION | Ecotoxic effects: no data available |
|-------------------|--|
| | |
| CONTACT POINT | Walker Ceramics 5 McLellan Street Bayswater Victoria 3153, Australia |
| | Telephone (03) 8761 6322 Fax (03) 8761 6344 |
| | Email sales@walkerceramics.com.au Website www.walkerceramics.com.au |
| | Date Of Issue: March 2019 |

This MSDS summarises, at the date of issue, our best knowledge of the health & safety hazard information for this product, and in particular how to safely handle and use this product in the workplace. Since Walker Ceramics and its agents cannot anticipate or control the conditions under which this product may be used, each user must prior to usage, review this MSDS in the context of how the user intends to handle and use this product in the workplace. If clarification or further information is needed to ensure that an appropriate assessment can be made, the user should contact us.

Our responsibility for products sold, is subject to our standard terms and conditions, a copy of which is sent to our customers and is also available upon request.